

TOWER SERIES



R410A
REFRIGERANT



AST-24AI

- Designed with an emphasis on aesthetics
- Usable for larger areas such as offices, meeting rooms, restaurants etc.
- Turbo heating and cooling
- Equipped with horizontal and vertical electric louver
- Self-diagnosis function
- Intelligent defrost system
- WiFi control
- Controlled by built-in or remote controller



DC INVERTER

TECHNICAL PARAMETERS

| MODEL | AST-24AI | | | |
|---|----------|-------|-------------------------|--|
| Capacity cooling / heating | KW | | 7,2 / 7,5 | |
| Power supply | Hz / V | | 1~ / 50 / 220-240 | |
| SEER / SCOP | - | | 6,1 / 4,0 | |
| Sound pressure level at 1m | ID | dB(A) | 49 / 45 / 42 / 39 | |
| | OD | dB(A) | 60 | |
| Dimension (w x h x d)/Net weight | ID | mm/kg | 507 x 1770 x 320 / 40,0 | |
| | OD | mm/kg | 955 x 700 x 396 / 53,5 | |
| Operating temperature range cooling/heating | °C | | -15 ~ 48 / -15 ~ 24 | |

For detailed technical parameters see technical part of catalogue. This catalogue sheet does not apply to project documentation.
Contains fluorinated greenhouse gases covered by the Kyoto Protocol. R410A (50% HFC-32, 50% HFC-125), GWP of refrigerant used: 2088.